


### Data Sheet

**Type Number** ..... 30395  
**Designation IEC** ..... SR 57  
**System** ..... Silver oxide / Zinc /  
 KOH - Electrolyte



**Nominal Voltage** ..... 1,55 V  
**Typical Capacity C** ..... 48 mAh  
 Load 13 kOhm, at 20°C down to 1.2 V

**Weight (approx.)** ..... 0,75 g  
**Volume** ..... 0,17 ccm  
**Coding**..... Date of Manufacturing  
 Month / Year

<b>Temperature Ranges</b>	min	max.
Storage .....	-10°C	65°C
Discharge .....	-10°C	65°C

<b>Dimensions</b>	min	max.
Diameter (Ø).....	9,15	9,5
Height A/(B) .....	2,4	2,7

**Segment** ..... Watch

### Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	1.2 V
Continuous 24h/d,7d/w	13000 Ω	Time:	400 h
		Capacity [mAh]:	48
		Energy [mWh]:	74

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst  
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!  
 Date of issue: 2012-04-12