
EcoTank ET-4750



DATASHEET



























This next generation EcoTank is a fast 4-in-1 with a 250-sheet paper tray. It can reduce printing costs by 74% on average¹.

Ultra-low cost

EcoTank can slash printing costs by 74% on average¹ thanks to its innovative design. It features an ultra-high-capacity ink tank that completely removes the need for cartridges, plus it comes with three years' worth of ink² included in the box. This model comes with an additional set of ink bottles.

Print thousands of pages

Get more prints between refills. Thanks to the ink included in the box, it can print 14,000 pages in black and 11,200 in colour³.

Discover the next generation of EcoTank

With the ink tank now housed at the front, EcoTank is more compact and easier to use than ever before. Protecting you against leaks and spills, it features an enhanced ink filling system engineered for mess-free refills. The new bottles also incorporate a mechanism to ensure that only the correct colours are inserted.

Business quality features

Produce crisp and clear texts thanks to the PrecisonCore printhead and Epson's genuine dye and pigment inks. Designed for business, it offers fax, a 250-sheet tray, double-sided printing, fast print speeds of 15ppm⁴ and a 30 page automatic document feeder (ADF). It's also backed by a three year warranty (upon registration).

Print from almost anywhere

With Wi-Fi and Wi-Fi Direct, send documents to print from smart devices using the Epson iPrint⁵ app. It can even receive files from almost anywhere in the world via Epson Email Print⁵.

KEY FEATURES

- Ultra-low-cost per page
 Reduce printing costs by 74%¹
- Three years worth of ink²included Print up to 14,000 pages in black and 11,200 pages in colour³
- Next generation ink filling system
 Enjoy hassle and mess-free refills with the enhanced ink bottles
- Mobile printing and connectivity Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps⁵
- Designed for business
 250 sheet front tray, fax, 30 page ADF and double-sided printing



PRODUCT SPECIFICATIONS

GENERAL

Interfaces WiFi, USB, Ethernet, Wi-Fi Direct

Energy Use 13 W (standalone copying, ISO/IEC 24712 pattern), 1.5 W (sleep mode), ENERGY STAR®

Product dimensions 375 x 347 x 231 mm (Width x Depth x Height)

Product weight 4.7 kg

Noise Level 5.1 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 37 dB (A) with Epson

Premium Glossy Photo Paper / Photo RPM mode

Compatible Operating Mac OS X 10.6.8 or later, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP,

XP Professional x64 Edition Systems

WLAN Security WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)

Mobile and Cloud printing Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,

services Google Cloud Print

TECHNOLOGY

PrecisionCore™ Print Head **Printing Method**

Minimum Droplet Size 3.3 pl. With Variable-Sized Droplet Technology

Ink Technology Pigment black and Dye colour Inks

Printing Resolution 4,800 x 1,200 dpi

PRINT

Printing Speed ISO/IEC 24734 15 pages/min Monochrome, 8 pages/min Colour

Maximum Printing Speed 20 pages/min Colour (plain paper), 33 pages/min Monochrome (plain paper)

Black, Cyan, Yellow, Magenta

For detailed information on printing speeds please visit http://www.epson.eu/testing.

SCAN

Scanning Resolution 1.200 dpi x 2.400 dpi (Horizontal x Vertical)

Scanner type Contact image sensor (CIS)

Fax speed dials (max) 60 names and numbers

Page memory Up to 100 pages (ITU-T No.1 chart)

Fax Functions PC Fax. Auto Redial. Address Book. Delay Send. Broadcast Fax

PAPER / MEDIA HANDLING

Number of paper trays

Paper Formats A4, A5, A6, B5, C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter Legal, 9 x 13 cm, 10 x

15 cm, 13 x 18 cm, 13 x 20 cm, 20 x 25 cm, 100 x 148 mm, 16:9. User defined

Duplex Yes (A4, plain paper)

Print Margin 0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm

top, left, right, bottom.)

Automatic Document Feeder 30 pages

Paper Tray Capacity 250 Sheets Standard, 20 Photo Sheets

Media Handling Auto Sheet Feeder, Automatic duplex (A4, plain paper)

OTHER FEATURES

LCD screen Type: Colour, Touchscreen, Diagonal: 6.1 cm

LOGISTICS INFORMATION

SKU	C11CG19401CE
EAN code	8715946650234
Country of Origin	Philippines

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742

Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

www.epson.co.uk www.epson.ie

EcoTank ET-4750

WHAT'S IN THE BOX

- Warranty document
- Main unit
- Power cable
- Setup guide
- Software (CD)
- 2 full sets of ink (Bk 127ml, CMY -70ml)

INK CARTRIDGE COMPATIBILITY

102

102

102

102



INK BOTTLE YIELD DATA

	•	• • •
Included	14,000 pages*	11,200 pages*
Replacement	7,500 pages*	6,000 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

- 1. Average number of cartridges/savings for printing the number of pages using the bundled ink bottles with the EcoTank range, including hardware price. Comparison made on the average of the A4 EcoTank range versus the average of the top 10 best-selling models in Western Europe, in the period April 2016 – March 2017, as tracked by GfK. Printing costs calculated on the proportion of Standard and XL cartridges as tracked by GfK for the same reference period for the Western European market, using average retail prices. Ink cartridge yields as communicated by the manufacturer's websites.
- 2. Based on an average print volume of 140 pages per month and considering the lowest yield produced from the first
- 3. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712. Quoted yields are NOT based on ISO/IEC24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set car be lower.
 4. Determined in accordance with ISO/IEC 24734 showing
- the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing
- 5. Requires a wireless connection to the internet. For more information, supported languages and devices please visit www.epsonconnect.eu

